



SJ3-VP

3-х струйная форсунка Sj3 обеспечивает трехструйное прямое внесение КАС и жидких удобрений.

Рекомендуемое давление


1,5-4 бар

Распылитель	Давление, бар	Расход, л/мин	Скорость движения, км/ч															
			6	8	10	11	12	13	14	15	16	17	18	20	22	24	26	30
			Норма расхода, литров на гектар															
SJ3-015	1,5	0,44	88	66	53	48	44	41	38	35	33	31	29	26	24	22	20	18
	2,0	0,50	100	75	60	55	50	46	43	40	38	35	33	30	27	25	23	20
	2,5	0,54	108	81	65	59	54	50	46	43	41	38	36	32	29	27	25	22
	3,0	0,58	116	87	70	63	58	54	50	46	44	41	39	35	32	29	27	23
	4,0	0,65	130	98	78	71	65	60	56	52	49	46	43	39	35	33	30	26
SJ3-02	1,5	0,57	114	86	68	62	57	53	49	46	43	40	38	34	31	29	26	23
	2,0	0,64	128	96	77	70	64	59	55	51	48	45	43	38	35	32	30	26
	2,5	0,70	140	105	84	76	70	65	60	56	53	49	47	42	38	35	32	28
	3,0	0,78	156	117	94	85	78	72	67	62	59	55	52	47	43	39	36	31
	4,0	0,85	170	128	102	93	85	78	73	68	64	60	57	51	46	43	39	34
SJ3-03	1,5	0,91	182	137	109	99	91	84	78	73	68	64	61	55	50	46	42	36
	2,0	1,01	202	152	121	110	101	93	87	81	76	71	67	61	55	51	47	40
	2,5	1,10	220	165	132	120	110	102	94	88	83	78	73	66	60	55	51	44
	3,0	1,18	236	177	142	129	118	109	101	94	89	83	79	71	64	59	54	47
	4,0	1,31	262	197	157	143	131	121	112	105	98	92	87	79	71	66	60	52
SJ3-04	1,5	1,17	234	176	140	128	117	108	100	94	88	83	78	70	64	59	54	47
	2,0	1,32	264	198	158	144	132	122	113	106	99	93	88	79	72	66	61	53
	2,5	1,45	290	218	174	158	145	134	124	116	109	102	97	87	79	73	67	58
	3,0	1,56	312	234	187	170	156	144	134	125	117	110	104	94	85	78	72	62
	4,0	1,75	350	263	210	191	175	162	150	140	131	124	117	105	95	88	81	70
SJ3-05	1,5	1,42	284	213	170	155	142	131	122	114	107	100	95	85	77	71	66	57
	2,0	1,63	326	245	196	178	163	150	140	130	122	115	109	98	89	82	75	65
	2,5	1,82	364	273	218	199	182	168	156	146	137	128	121	109	99	91	84	73
	3,0	1,96	392	294	235	214	196	181	168	157	147	138	131	118	107	98	90	78
	4,0	2,18	436	327	262	238	218	201	187	174	164	154	145	131	119	109	101	87
SJ3-06	1,5	1,69	338	254	203	184	169	156	145	135	127	119	113	101	92	85	78	68
	2,0	1,97	394	296	236	215	197	182	169	158	148	139	131	118	107	99	91	79
	2,5	2,21	442	332	265	241	221	204	189	177	166	156	147	133	121	111	102	88
	3,0	2,40	480	360	288	262	240	222	206	192	180	169	160	144	131	120	111	96
	4,0	2,63	526	395	316	287	263	243	225	210	197	186	175	158	143	132	121	105
SJ3-08	1,5	2,32	464	348	278	253	232	214	199	186	174	164	155	139	127	116	107	93
	2,0	2,74	548	411	329	299	274	253	235	219	206	193	183	164	149	137	126	110
	2,5	2,94	588	441	353	321	294	271	252	235	221	208	196	176	160	147	136	118
	3,0	3,13	626	470	376	341	313	289	268	250	235	221	209	188	171	157	144	125
	4,0	3,50	700	525	420	382	350	323	300	280	263	247	233	210	191	175	162	140
SJ3-010	1,5	2,73	546	410	328	298	273	252	234	218	205	193	182	164	149	137	126	109
	2,0	3,30	660	495	396	360	330	305	283	264	248	233	220	198	180	165	152	132
	2,5	3,55	710	533	426	387	355	328	304	284	266	251	237	213	194	178	164	142
	3,0	3,91	782	587	469	427	391	361	335	313	293	276	261	235	213	196	180	156
	4,0	4,44	888	666	533	484	444	410	381	355	333	313	296	266	242	222	205	178
SJ3-015	1,5	3,91	782	587	469	427	391	361	335	313	293	276	261	235	213	196	180	156
	2,0	4,64	928	696	557	506	464	428	398	371	348	328	309	278	253	232	214	186
	2,5	5,29	1058	794	635	577	529	488	453	423	397	373	353	317	289	265	244	212
	3,0	5,86	1172	879	703	639	586	541	502	469	440	414	391	352	320	293	270	234
	4,0	6,76	1352	1014	811	737	676	624	579	541	507	477	451	406	369	338	312	270

Данные в таблице указаны для следующих условий: интервал расстановки распылителей - 50 см, жидкость - вода, t = 21 °C