


SJ7A

Идеально подходит для внесения жидких удобрений.

 Рекомендуемое
давление

1,5-4 бар

Распылитель	Давление, бар	Расход, л/мин	Скорость движения, км/ч															
			6	8	10	11	12	13	14	15	16	17	18	20	22	24	26	30
			Норма расхода, литров на гектар															
SJ7-015	1,5	0,39	78	59	47	43	39	36	33	31	29	28	26	23	21	20	18	16
	2,0	0,46	92	69	55	50	46	42	39	37	35	32	31	28	25	23	21	18
	2,5	0,52	104	78	62	57	52	48	45	42	39	37	35	31	28	26	24	21
	3,0	0,57	114	86	68	62	57	53	49	46	43	40	38	34	31	29	26	23
4,0	0,67	134	101	80	73	67	62	57	54	50	47	45	40	37	34	31	27	
SJ7-02	1,5	0,55	110	83	66	60	55	51	47	44	41	39	37	33	30	28	25	22
	2,0	0,64	128	96	77	70	64	59	55	51	48	45	43	38	35	32	30	26
	2,5	0,72	144	108	86	79	72	66	62	58	54	51	48	43	39	36	33	29
	3,0	0,80	160	120	96	87	80	74	69	64	60	56	53	48	44	40	37	32
4,0	0,93	186	140	112	101	93	86	80	74	70	66	62	56	51	47	43	37	
SJ7-03	1,5	0,87	174	131	104	95	87	80	75	70	65	61	58	52	47	44	40	35
	2,0	1,00	200	150	120	109	100	92	86	80	75	71	67	60	55	50	46	40
	2,5	1,10	220	165	132	120	110	102	94	88	83	78	73	66	60	55	51	44
	3,0	1,18	236	177	142	129	118	109	101	94	89	83	79	71	64	59	54	47
4,0	1,31	262	197	157	143	131	121	112	105	98	92	87	79	71	66	60	52	
SJ7-04	1,5	1,17	234	176	140	128	117	108	100	94	88	83	78	70	64	59	54	47
	2,0	1,33	266	200	160	145	133	123	114	106	100	94	89	80	73	67	61	53
	2,5	1,45	290	218	174	158	145	134	124	116	109	102	97	87	79	73	67	58
	3,0	1,55	310	233	186	169	155	143	133	124	116	109	103	93	85	78	72	62
4,0	1,72	344	258	206	188	172	159	147	138	129	121	115	103	94	86	79	69	
SJ7-05	1,5	1,49	298	224	179	163	149	138	128	119	112	105	99	89	81	75	69	60
	2,0	1,68	336	252	202	183	168	155	144	134	126	119	112	101	92	84	78	67
	2,5	1,83	366	275	220	200	183	169	157	146	137	129	122	110	100	92	84	73
	3,0	1,95	390	293	234	213	195	180	167	156	146	138	130	117	106	98	90	78
4,0	2,16	432	324	259	236	216	199	185	173	162	152	144	130	118	108	100	86	
SJ7-06	1,5	1,77	354	266	212	193	177	163	152	142	133	125	118	106	97	89	82	71
	2,0	2,01	402	302	241	219	201	186	172	161	151	142	134	121	110	101	93	80
	2,5	2,19	438	329	263	239	219	202	188	175	164	155	146	131	119	110	101	88
	3,0	2,35	470	353	282	256	235	217	201	188	176	166	157	141	128	118	108	94
4,0	2,61	522	392	313	285	261	241	224	209	196	184	174	157	142	131	120	104	
SJ7-08	1,5	2,28	456	342	274	249	228	210	195	182	171	161	152	137	124	114	105	91
	2,0	2,66	532	399	319	290	266	246	228	213	200	188	177	160	145	133	123	106
	2,5	2,94	588	441	353	321	294	271	252	235	221	208	196	176	160	147	136	118
	3,0	3,15	630	473	378	344	315	291	270	252	236	222	210	189	172	158	145	126
4,0	3,46	692	519	415	377	346	319	297	277	260	244	231	208	189	173	160	138	
SJ7-010	1,5	2,84	568	426	341	310	284	262	243	227	213	200	189	170	155	142	131	114
	2,0	3,32	664	498	398	362	332	306	285	266	249	234	221	199	181	166	153	133
	2,5	3,67	734	551	440	400	367	339	315	294	275	259	245	220	200	184	169	147
	3,0	3,94	788	591	473	430	394	364	338	315	296	278	263	236	215	197	182	158
4,0	4,33	866	650	520	472	433	400	371	346	325	306	289	260	236	217	200	173	
SJ7-015	1,5	4,09	818	614	491	446	409	378	351	327	307	289	273	245	223	205	189	164
	2,0	4,82	964	723	578	526	482	445	413	386	362	340	321	289	263	241	222	193
	2,5	5,40	1080	810	648	589	540	498	463	432	405	381	360	324	295	270	249	216
	3,0	5,87	1174	881	704	640	587	542	503	470	440	414	391	352	320	294	271	235
4,0	6,58	1316	987	790	718	658	607	564	526	494	464	439	395	359	329	304	263	

Данные в таблице указаны для следующих условий: интервал расстановки распылителей - 50 см, жидкость - вода, t = 21 °C