



XR110

XR110 VP - один из самых популярных распылителей для внесения СЗР. Спектр капель очень сильно изменяется в зависимости от давления.

Рекомендуемое давление



1 - 4 бар

Распылитель	Давление, бар	Расход, л/мин	Скорость движения, км/ч															
			6	8	10	11	12	13	14	15	16	17	18	20	22	24	26	30
			Норма расхода, литров на гектар															
XR 11001	1,0	0,23	46	35	28	25	23	21	20	18	17	16	15	14	13	12	11	9
	1,5	0,28	56	42	34	31	28	26	24	22	21	20	19	17	15	14	13	11
	2,0	0,32	64	48	38	35	32	30	27	26	24	23	21	19	17	16	15	13
	2,5	0,36	72	54	43	39	36	33	31	29	27	25	24	22	20	18	17	14
	3,0	0,39	78	59	47	43	39	36	33	31	29	28	26	23	21	20	18	16
4,0	0,45	90	68	54	49	45	42	39	36	34	32	30	27	25	23	21	18	
XR 110015	1,0	0,34	68	51	41	37	34	31	29	27	26	24	23	20	19	17	16	14
	1,5	0,42	84	63	50	46	42	39	36	34	32	30	28	25	23	21	19	17
	2,0	0,48	96	72	58	52	48	44	41	38	36	34	32	29	26	24	22	19
	2,5	0,54	108	81	65	59	54	50	46	43	41	38	36	32	29	27	25	22
	3,0	0,59	118	89	71	64	59	54	51	47	44	42	39	35	32	30	27	24
4,0	0,68	136	102	82	74	68	63	58	54	51	48	45	41	37	34	31	27	
XR 11002	1,0	0,46	92	69	55	50	46	42	39	37	35	32	31	28	25	23	21	18
	1,5	0,56	112	84	67	61	56	52	48	45	42	40	37	34	31	28	26	22
	2,0	0,65	130	98	78	71	65	60	56	52	49	46	43	39	35	33	30	26
	2,5	0,72	144	108	86	79	72	66	62	58	54	51	48	43	39	36	33	29
	3,0	0,79	158	119	95	86	79	73	68	63	59	56	53	47	43	40	36	32
4,0	0,91	182	137	109	99	91	84	78	73	68	64	61	55	50	46	42	36	
XR 11003	1,0	0,68	136	102	82	74	68	63	58	54	51	48	45	41	37	34	31	27
	1,5	0,83	166	125	100	91	83	77	71	66	62	59	55	50	45	42	38	33
	2,0	0,96	192	144	115	105	96	89	82	77	72	68	64	58	52	48	44	38
	2,5	1,08	216	162	130	118	108	100	93	86	81	76	72	65	59	54	50	43
	3,0	1,18	236	177	142	129	118	109	101	94	89	83	79	71	64	59	54	47
4,0	1,36	272	204	163	148	136	126	117	109	102	96	91	82	74	68	63	54	
XR 11004	1,0	0,91	182	137	109	99	91	84	78	73	68	64	61	55	50	46	42	36
	1,5	1,12	224	168	134	122	112	103	96	90	84	79	75	67	61	56	52	45
	2,0	1,29	258	194	155	141	129	119	111	103	97	91	86	77	70	65	60	52
	2,5	1,44	288	216	173	157	144	133	123	115	108	102	96	86	79	72	66	58
	3,0	1,58	316	237	190	172	158	146	135	126	119	112	105	95	86	79	73	63
4,0	1,82	364	273	218	199	182	168	156	146	137	128	121	109	99	91	84	73	
XR 11005	1,0	1,14	228	171	137	124	114	105	98	91	86	80	76	68	62	57	53	46
	1,5	1,39	278	209	167	152	139	128	119	111	104	98	93	83	76	70	64	56
	2,0	1,61	322	242	193	176	161	149	138	129	121	114	107	97	88	81	74	64
	2,5	1,80	360	270	216	196	180	166	154	144	135	127	120	108	98	90	83	72
	3,0	1,97	394	296	236	215	197	182	169	158	148	139	131	118	107	99	91	79
4,0	2,27	454	341	272	248	227	210	195	182	170	160	151	136	124	114	105	91	
XR 11006	1,0	1,37	274	206	164	149	137	126	117	110	103	97	91	82	75	69	63	55
	1,5	1,38	276	207	166	151	138	127	118	110	104	97	92	83	75	69	64	55
	2,0	1,94	388	291	233	212	194	179	166	155	146	137	129	116	106	97	90	78
	2,5	2,16	432	324	259	236	216	199	185	173	162	152	144	130	118	108	100	86
	3,0	2,37	474	356	284	259	237	219	203	190	178	167	158	142	129	119	109	95
4,0	2,74	548	411	329	299	274	253	235	219	206	193	183	164	149	137	126	110	
XR 11008	1,0	1,82	364	273	218	199	182	168	156	146	137	128	121	109	99	91	84	73
	1,5	2,23	446	335	268	243	223	206	191	178	167	157	149	134	122	112	103	89
	2,0	2,58	516	387	310	281	258	238	221	206	194	182	172	155	141	129	119	103
	2,5	2,88	576	432	346	314	288	266	247	230	216	203	192	173	157	144	133	115
	3,0	3,16	632	474	379	345	316	292	271	253	237	223	211	190	172	158	146	126
4,0	3,65	730	548	438	398	365	337	313	292	274	258	243	219	199	183	168	146	

Данные в таблице указаны для следующих условий: интервал расстановки распылителей - 50 см, жидкость - вода, t = 21 °C